



# **WARNING!**

**Failure to comply with these warnings and instructions may cause SERIOUS INJURY, DEATH, or DAMAGE TO YOUR PRODUCT.**

Be sure to read this manual carefully before using your DVO suspension. Throughout this manual, reference is made that “an accident” could occur. Any accident may cause damage to the product, SERIOUS INJURY, OR DEATH.

These instructions contain important information about the correct installation, guidelines for set-up, service and maintenance of your suspension. Nevertheless, please be informed that special knowledge and tools are essential to install, service and to maintain DVO Suspension. Common mechanical knowledge may not be sufficient to repair, service or maintain your suspension. Therefore we strongly recommend getting your suspension installed, serviced and/or maintained by a trained and qualified bicycle mechanic. Improper installation, service or maintenance can result in an accident.

Forks and rear shocks contain fluids and air under extreme pressure. DO NOT attempt to disassemble any portion of a DVO Suspension product unless instructed to do so by a DVO Suspension authorized technician.

Only use genuine DVO Suspension replacement parts. Modification, improper service, or the use of aftermarket replacement or spare parts may result in an accident and VOIDS the warranty of your product.

DVO Suspension forks and rear shocks are designed for the usage by a single rider only.

DO NOT use DVO Suspension products on any powered vehicle that is not a pedal-assist Class-1 or Class-3 e Bike.

Always be equipped with proper safety gear. This includes a properly fitted and fastened helmet. According to your riding style you should use additional safety protection. Make sure your equipment is in flawless condition.

Make sure you select the correct fork and rear shock according to your frame manufacturer specification. Installing suspension that does not match the geometry of your frame could result in a failure of the suspension itself and void the suspension warranty. Installing a fork or rear shock not designed for your frame will change the geometry and handling of your bike. Learn how to ride and train your skills. Know your limits and never ride beyond those.

Study all other manuals provided with your bicycle and make yourself familiar with all components mounted to your bike.

## PRE-RIDE SAFETY CHECK


1. DO NOT ride your bicycle if any one of the following test criteria is not passed! Riding your bike without eliminating any defect or carrying out the necessary adjustments can result in an accident, SERIOUS INJURY OR DEATH.
2. Do you notice any cracks, dents, bent, or tarnished parts of your suspension fork or shock, or any other part of your bicycle? If so, please contact a trained and qualified bicycle mechanic to check your fork, shock, seat post, saddle, and complete bike.
3. Do you notice any oil leaking from your fork and/or shock? If so, please consult a trained and qualified bicycle mechanic to check your suspension and bike before riding.
4. Make sure your wheel is attached and centered properly in order to avoid any contact with the suspension fork or brake system.
5. Make sure your axle system is secure. There should be no play between the hub and fork lower.
6. Make sure your brakes are properly installed, adjusted, and work properly. This also applies to every other part of your bike like handlebars, pedals, cranks arms, seat post, saddle, etc.
7. Check the cable length and routing of your braking components. Make sure they do not interfere with your steering actions or full compression and extension of your suspension.
8. Check your shock hardware and ensure there is no play between the shock and mounting surfaces. Ensure your shock hardware is tightened to the bike manufacturer's recommend torque before riding.

## TOOLS NEEDED FOR SETUP

1. **Shock Pump**
2. **2.5mm, 5mm Allen Key**
3. **Tape Measure or Calipers**
4. **27mm Socket (chamferless)**
5. **Slikoleum or Equivilent Grease**
6. **Protective eyewear**

## SOME HELPFUL TIPS BEFORE YOU GET STARTED

1. All of these settings are just starting points to get you close. Don't be afraid to use your adjusters or change up your settings to make it perfect for you.
2. Write down your settings! Modern suspension forks have a ton of adjustment which is awesome, but you can get lost. When you find a good spot, write it down so you can always go back to it.
3. Dedicate time to setting your bike up for the trail, not the parking lot. It's a good idea to get out on the trail and find a section you can repeat. Try different settings to truly feel what the adjusters are doing. Once you truly understand what they do and feel like, you'll know when to use them in any situation.
4. Balance is key! This is a big one. Try your best to get your fork and shock feeling equal. If the rebound in the rear shock is way faster than the fork, the bike won't have a very predic cable ride. Feel to make sure the rebound, spring rate, and compression are having similar feelings front and back. This will provide a predictable and confidence inspiring ride.
5. If you have questions, don't hesitate to ask. Give us a call, shoot us an email, we'll get you dialed in! [cs@dvosuspension.com](mailto:cs@dvosuspension.com)



# SETTING SAG & AIR PRESSURE



## What is SAG?

SAG is the amount your fork compresses under your body weight (don't forget to include your riding gear), also referred to as Rider Weight. Remember that these are only starting points and adjustments will vary based on rider ability, trail conditions and personal preference.

After you are done setting up your suspension fork according to the recommended base settings, check your SAG to make sure you are within the recommended SAG settings.

The recommended SAG is 15% - 30%. Setting proper SAG is the only way to find the right air pressure for your fork. Refer to the chart below to find the proper SAG.



## Can SAG effect the handling?

It is very beneficial to test different SAG settings for various riding conditions. Changing the amount of SAG on your fork will change the geometry of your bike.

Riders that make high speed stability a priority can run less SAG. This will keep the front end of the bike high under braking and rough sections but comfort and cornering traction will be compromised.

Riders that want to have a comfortable ride with great cornering traction should run more SAG (around 30%).

### **WARNING!**

**DO NOT exceed maximum air pressure of 100PSI. Failure to comply with these instructions may cause SERIOUS INJURY, DEATH, or DAMAGE TO YOUR PRODUCT.**

### SAG Measurement in MM

MAX Travel	15% SAG	20% SAG	30% SAG
140mm	21mm	28mm	42mm
150mm	22.5mm	30mm	45mm
160mm	24mm	32mm	48mm
170mm	25.5mm	34mm	51mm

## Important Note:

Our dual chamber air system needs to equalize pressure between positive and negative chambers. Inflate the fork to your desired pressure then compress the fork roughly 25mm. You should hear an audible air transferring "hissing" sound. Once air transfer is achieved, set your pressure to the desired PSI. Check your pressure with the fork un-weighted and at full extension.


### Air Pressure Base Setting Chart (Diamond 36)

Rider Weight		Air Pressure (psi)										
lbs	kg	50	55	60	65	70	75	80	85	90	95	100 MAX
120-139	54-63	PLUSH		FIRM								
140-159	64-72		PLUSH		FIRM							
160-179	73-81			PLUSH		FIRM						
180-199	82-90				PLUSH		FIRM					
200-219	91-100					PLUSH		FIRM				
220-239	101-108						PLUSH		FIRM			
240-249	109-113							PLUSH		FIRM		
250-259	114-117									PLUSH		FIRM

## REBOUND: EXPLAINED

Rebound controls the speed at which the fork extends after compression. Rebound damping control is relative to the amount of air pressure used.

Start with your rebound closed (all the way clockwise) then adjust out to make it faster. Each click out (counter-clockwise) is your rebound setting. Use the chart to find a good starting position.



**Fastest Rebound Setting**  
(Counter-Clockwise)

**Slowest Rebound Setting**  
(Clockwise)

Rebound Base Setting Chart (Diamond 36)

Air Pressure	Rebound Clicks (out from closed)														
	PSI	25	24	22	20	18	16	14	12	10	8	6	4	2	0
50-55		FAST		SLOW											
55-60			FAST		SLOW										
60-65				FAST		SLOW									
65-70					FAST		SLOW								
70-75						FAST		SLOW							
75-80							FAST		SLOW						
80-85								FAST		SLOW					
90-95									FAST		SLOW				
100										FAST		SLOW			

## IS MY SETTING TOO FAST OR SLOW?

If rebound is too fast, your wheel will fall into more holes, instead of skipping over the top of them. Handling will feel twitchy and hard to control, it will be easier to be thrown out of control on jumps and landings.

If rebound is set too slow it will pack on successive hits because the fork cannot extend fast enough keeping you in the mid stroke. This will result in the wheel going deeper into the travel on every hit and riding towards the end stroke. The result will be a harsh feeling and loss of traction.


## LSC: EXPLAINED

The CORE Model forks come with a full range low speed compression. Use this feature to add more support for body movements on the bike. This will help the front-end stand up taller and reduce the potential for “diving” under braking.

We recommend starting with your LSC setting in the middle of the range. If you need a firmer or softer ride, go one to two clicks in either direction until you're comfy.



LSC Base Setting Chart



## WHAT IS IT EXACTLY?

Low speed compressions controls the slower vertical movements such as climbing or slower paced trails and bumpy whoop sections. A good example of low speed is rolling slowly over a large rock and riding to its downside, this is where the suspension will fully compress but at a slower rate and low speed compression circuit comes into play. LSC refers to the shaft speed of the suspension and not the actual riding speed. LS compression is best controlled through a low speed oil circuit and or shim stack.

## TOO MUCH, OR TOO LITTLE DAMPING?

Too much Low Speed Compression will result in harshness over small bumps and traction will be reduced. Turning performance may also suffer because the suspension will ride too high in its travel. The ride may become harsh.


Not enough Low Speed Compression will result in the front end diving to quickly under braking. The suspension will have a mushy feeling and may bottom out too easily.



## AXLE INSTALLATION

Your new Diamond 36 comes with a thru-axle system. Proper installation is extremely important for safety and function. Follow the steps below to perform installation correctly.

1. Install the wheel into the dropouts and center.
2. Insert the axle into the drive-side dropout, through the hub, and engage the threads in the non-drive side dropout
3. Tighten the axle with a 5mm allen key and torque to **10 Nm**.



### **⚠ WARNING!**


Before every ride, always ensure that your thru-axle is torqued to spec. Failure to do so can lead to loss of control of the bicycle, which can result in **SEVERE INJURY OR DEATH**.

## MOUNTING DISC BRAKES



Your new Diamond 36 comes with a 180mm post mounts to allow you to bolt your caliper directly to the fork and utilize a 180mm rotor.

If using a different sized rotor (not 180mm), you will need to source the appropriate caliper spacer and bolts. Contact the brake manufacturer for further information.



### **⚠ WARNING!**

Follow your brake manufacturer's installation instructions for proper installation and adjustment of the brake system. Failure to properly install and adjust your brakes can lead to a loss of control of the bicycle which can result in **SEVERE INJURY OR DEATH**.

Changing volume spacers is an easy way to tune the air spring of your Diamond CORE fork. This can provide an increase in mid-stroke and bottom-out resistance.


How do I know when to use a volume spacer? Always start with your SAG as the reference point. If SAG is set correctly and you are using full travel too easily, install one volume spacer and test ride. Repeat until the appropriate travel is used. **A maximum of 6 volume spacers can be used.**

## HOW TO INSTALL VOLUME SPACERS

1. Make sure your fork is clean and free of any dirt or contamination.
2. **Release ALL air pressure** from fork.
3. Using a chamferless 27mm socket, loosen air side top cap **(A)** and remove.
4. Press on the desired amount of volume spacers **(C)** into the air side top cap **(A)**.
5. Re-install air side top cap **(A)** into the stanchion. **Tighten to 20 Nm.**
6. Make sure the air side top cap o-ring **(B)** has sufficient grease. We recommend Slikoleum or an equivalent grease.
7. Using a shock pump, inflate the fork to your desired air pressure.

### **WARNING!**

Always refer to the proper installation instructions stated above. Failure to properly install and adjust your volume spacers can result in **SEVERE INJURY OR DEATH.**



Additional Information on the Next Page.....

## AIR VOLUME TUNING

### Important Note:


Air springs are always progressive which means the force needed to compress the fork is always increasing through the stroke. A higher air pressure means the fork will naturally be more progressive. A lighter pressure will be less progressive. Lighter riders may need to use more volume spacers. And heavier riders may need to use less.

#### Volume Spacer Configurations

Travel	Factory Installed Volume Spacers	Max Volume Spacers
140-170mm	0	6

#### Air Spring Graph (for all Diamond 36 models)

0 Spacers   1 Spacer   2 Spacers   3 Spacers   4 Spacers   5 Spacers   6 Spacers



## FENDER INSTALLION



Your new Diamond 36 CORE comes with a large coverage fender. Proper installation is key to avoid potential damage. Slide the fender through the underside of the arch and fasten with 3x 2.5mm hex bolts. DO NOT over torque the mounting bolts, damage to the casting may occur.

Always check for at least 6mm of tire clearance from the tallest point of the tire to the underside of the fender. It's also a good idea to periodically check to ensure the fender bolts are tight.

Torque spec for fender bolts is a maximum of **5 kgf·cm**.



Refer to owner's manual for maximum tire specifications and clearance.